



DF FIX SP

Depureco Industrial Vacuums USA

19121 Marketplace Avenue, Building 1, Suite 165
Plum Creek Business Park • Kyle • TX 78640

www.depurecousa.com
info@depurecousa.com



8.5 HP
POWER

18,600 in²
FILTER

46 gal Bin
CAPACITY




**SP AUTOMATIC FILTER
CLEANING SYSTEM**

Adjustable
Air-operated
Automatic

**4X POLYESTER
CARTRIDGES**



18,600 in²



DETACHABLE CONTAINER



46 gal

**ELECTRICAL
PANEL**

With optional
remote control

ELECTRICAL FAN


480V
Max Airflow= 1,589 - 2,472 CFM



SPEC SHEET

	Units	DF FIX 55 SP	DF FIX 75 SP
Motors Type		Fan	Fan
Power	HP	8.5	9
Voltage Frequency	V/Hz	480/60	480/60
Maximum vacuum	inH2O	25.9	39.7
Maximum air flow	CFM	1,589	2,472
Inlet	Ø in	7.9	7.9
Noise level - (EN ISO 3744)	dB(A)	74	74
Bin capacity	gal	46	46
Dimensions	in	65.75 X 33.46	65.75 X 33.46
Height	in	77.95	77.95
Weight	lb	485	485
Primary filter			
Type		Cartridge	Cartridge
Surface area Diameter	in² in	18,600	18,600
(Class EN 60335-2-69)		M Class	M Class
Media		Polyester	Polyester
Filter cleaning		SP - Reverse pulse jet	SP - Reverse pulse jet
Absolute filter (optional)			
Surface area	in²	24,800	24,800
(Class - EN 1822)		H14	H14
Media		Fiberglass	Fiberglass


OPTIONAL FILTERS




ANT M
Antistatic filter



PTFE
PTFE filter



PTFE ANT
Antistatic PTFE filter



H14
HEPA secondary filter

OPTIONAL



GRD
Grounding



BX
AISI 304 stainless stell bin



LR
Remote control predisposition

ACCESSORIES



FLANGED CONE CONNECTION